

40kVA Soundproof Generator



Features

- Noise Level @ 1m, 73dBA (@7m, 61dBA)
- Autostart DSE CP with MCCB
- VELCB
- Micro Switch Protection over Buss Bar Door
- Oil Extraction Pump
- 3 Way Fuel Valve
- Battery Isolator
- Water Separator Std
- Cental Lifting Hook
- Fork Lift Pockets
- Fully Bunded

Options

- Bulk Fuel Tank
- Battery Charger

POWERMAIN LTD

Power Continuity Specialists

Powermain has a policy of continuous improvement and therefore reserve the right to change the specification without prior notice.
Unit 15 Hedgend Ind Est, Stuart Lane, St. Nicholas-At-Wade, Birchington, Kent CT7 0NB

Generating Set	50 Hz
Continuous Power	40 kVA
Standby Power	44 kVA
Noise Level @ 1m / 7m	73 dBA / 61 dBA
Power Factor	cos φ 0.8
Continuous Power	33 kW _e
Standby Power	36 kW _e
Amps 3 Phase	55 A
Fuel consumption 70% load	6.6 l/h
Engine	1500 rpm
Model	John Deere 3029TF158
Continuous Power	36 kW _m
Standby Power	40 kW _m
Aspiration	Turbocharged
Cooling System	Water
Speed Governor	Mechanical
Cylinder Number	3
Displacement	2,900 cm ³
Logistic Information	GX51JD
Fuel Tank	135 ltr
Weight (Wet)	1,155 kg
Dimensions (L x W x H)	196 x 98 x 148 cm
Control Panel	Deep Sea 7210
Auto Start	Standard



Deep Sea 7210 Control Panel

